



Technical Data

Project Name : Untitled project 2025-03-19 21:45:46.331	Project ID :
Company Name : Department : Phone number : e-mail address :	

Requested Data

Flow : 21.7 m ³ /h	Fluid : Water
Head : 25.71 m	Density : 0.9983 kg/dm ³
	Viscosity : 1.005 mm ² /s
	Temperature : 20 °C

Pump

Operating Data

Pump Model : ECW 32/160	Flow : 21.7 m ³ /h
Inlet / Outlet size : 50x32	Head : 25.71 m
Speed : 2900 1/min	Shutoff Head : 29.56 m
Direction of Rotation : Clockwise from the drive end	Shaft Power (BkW) : 2.551 kW
Impeller type : Radial impeller	End of Power curve : 2.903 kW
Impeller Diameter : 145.4 mm	Efficiency : 59.61 %
Min.Impeller Diameter : 136 mm	NPSHr Value : 3.144 m
Max.Impeller Diameter : 170 mm	Moment of Inertia : 0.074 kg m ²
Maximum Solid Size : 6.5 mm	Operating Pressure : 2.518 bar
Pump Weight (Approx) : 34 kg	Maximum Allowable Pressure : 2.895 bar
Pump Standard : EN 733	Minimum Continuous Flow : 6.542 m ³ /h

Motor

Frequency : 50 Hz	Speed : 2900 1/min
Phase : 3~	Degree of Protection : IP 55
Rated Voltage : 415 V	Insulation Class : F
Rated current : 7.1 A	Frame size : 100 L
Rated Power P2 : 3.7 kW	

Material of Construction

Flange Connections

Casing : ASTM A743 / A351 CF8	Suction Flange
Impeller : ASTM A743 / A351 CF8	Pressure rating : 16 bar
Stuffing Box : ASTM A743 / A351 CF8	Nominal pipe size : 50
Wear Ring : ASTM A743 / A351 CF8	Standard : PN 16
Bearing Frame : ASTM A48 class 30B	
Shaft : ASTM A276 AISI 304	Discharge Flange
Shaft Sleeve : ASTM A276 AISI 304	Pressure rating : 16 bar
Shaft seal : GLAND PACKING	Nominal pipe size : 32
	Standard : PN 16



C.R.I. PUMPS
Pumping trust. Worldwide.

Performance Curve

Pump Model
ECW 32/160

Project Name : Untitled project 2025-03-19 21:45:46.331

Project ID :


Company Name :

Department :

Phone number :

e-mail address :

Curve Tolerance ISO 9906 Grade 2B



Note:

- i. Performance is not guaranteed except for the rated point.
 - ii. Curves specified are as per Specific gravity and viscosity of water 1.0,
 - iii. Consider NPSH safety margin minimum of 0.5m .
- To select the motor size, read the value of the Power curve at the duty point



C.R.I. PUMPS
Pumping trust. Worldwide.

Dimensional Drawing

Pump Model
ECW 32/160

Project Name : Untitled project 2025-03-19 21:45:46.331


Project ID :

Company Name :

Department :

Phone number :

e-mail address :



In View of continuous developments, The information/specifications/Description/ Illustrations are subject to change without notice.

Dimensions in mm

a	80			H.D(Delivery)	19
b1	240			No.of Holes-Discharge	4
b2	210			No.of Holes-Suction	4
f	360			Nominal Size (ØA)	50
H	227			Nominal Size (ØB)	32
h2	160			P.C.D(Delivery)	100
ha	152			P.C.D(Suction)	125
L1	825				
L2	625				
Ø A	50				
Ø B	32				
S	14				
X	100				
Z	4				