



Technical Data

Project Name : Untitled project 2025-03-22 10:19:23.013	Project ID :
Company Name : Department : Phone number : e-mail address :	

Requested Data

Flow : 32.1 m³/h	Fluid : Water
Head : 92.38 m	Density : 0.9983 kg/dm³
	Viscosity : 1.005 mm²/s
	Temperature : 20 °C

Pump

Operating Data

Pump Model : ECW 32/250	Flow : 32.03 m³/h
Inlet / Outlet size : 50x32	Head : 91.98 m
Speed : 2900 1/min	Shutoff Head : 98 m
Direction of Rotation : Clockwise from the drive end	Shaft Power (BkW) : 15.01 kW
Impeller type : Radial impeller	End of Power curve : 17.8 kW
Impeller Diameter : 261 mm	Efficiency : 53.45 %
Min.Impeller Diameter : 209 mm	NPSHr Value : 6.503 m
Max.Impeller Diameter : 261 mm	Moment of Inertia : 0.3 kg m²
Maximum Solid Size : 5.5 mm	Operating Pressure : 9.008 bar
Pump Weight (Approx) : 57 kg	Maximum Allowable Pressure : 9.597 bar
Pump Standard : EN 733	Minimum Continuous Flow : 9.54 m³/h

Motor

Frequency : 50 Hz	Speed : 2900 1/min
Phase : 3~	Degree of Protection : IP 55
Rated Voltage : 415 V	Insulation Class : F
Rated current : 26.5 A	Frame size : 160 M
Rated Power P2 : 15 kW	

Material of Construction

Flange Connections

Casing : ASTM A743 / A351 CF8	Suction Flange
Impeller : ASTM A743 / A351 CF8	Pressure rating : 16 bar
Stuffing Box : ASTM A743 / A351 CF8	Nominal pipe size : 50
Wear Ring : ASTM A743 / A351 CF8	Standard : PN 16
Bearing Frame : ASTM A48 class 30B	
Shaft : ASTM A276 AISI 304	Discharge Flange
Shaft Sleeve : ASTM A276 AISI 304	Pressure rating : 16 bar
Shaft seal : GLAND PACKING	Nominal pipe size : 32
	Standard : PN 16



C.R.I. PUMPS
Pumping trust. Worldwide.

Performance Curve


Pump Model
ECW 32/250

Project Name : Untitled project 2025-03-22 10:19:23.013

Project ID :

Company Name :
Department :
Phone number :
e-mail address :

Curve Tolerance ISO 9906 Grade 2B



Note:

- Performance is not guaranteed except for the rated point.
 - Curves specified are as per Specific gravity and viscosity of water 1.0,
 - Consider NPSH safety margin minimum of 0.5m .
- To select the motor size, read the value of the Power curve at the duty point



C.R.I. PUMPS
Pumping trust. Worldwide.


Dimensional Drawing

Pump Model
ECW 32/250

Project Name : Untitled project 2025-03-22 10:19:23.013

Project ID :

Company Name :
Department :
Phone number :
e-mail address :



In View of continuous developments, The information/specifications/Description/ Illustrations are subject to change without notice.

Dimensions in mm

a	100			H.D(Delivery)	19
b1	380			H.D(Suction)	19
b2	350			No.of Holes-Discharge	4
f	360			No.of Holes-Suction	4
H	275			Nominal Size (ØA)	50
h2	225			Nominal Size (ØB)	32
hA	200			P.C.D(Delivery)	100
L1	1005			P.C.D(Suction)	125
L2	805				
L3	402.5				
Ø A	50				
Ø B	32				
S	14				
X	100				
Z	6				