



Technical Data

Project Name : Untitled project 2025-03-22 10:19:23.013	Project ID :
Company Name : Department : Phone number : e-mail address :	

Requested Data

Flow : 112 m ³ /h	Fluid : Water
Head : 63.25 m	Density : 0.9983 kg/dm ³
	Viscosity : 1.005 mm ² /s
	Temperature : 20 °C

Pump

Operating Data

Pump Model : ECW 65/200	Flow : 112 m ³ /h
Inlet / Outlet size : 80x65	Head : 63.25 m
Speed : 2900 1/min	Shutoff Head : 66.06 m
Direction of Rotation : Clockwise from the drive end	Shaft Power (BkW) : 23.83 kW
Impeller type : Radial impeller	End of Power curve : 29.67 kW
Impeller Diameter : 218.9 mm	Efficiency : 80.95 %
Min.Impeller Diameter : 176 mm	NPSHr Value : 4.049 m
Max.Impeller Diameter : 219 mm	Moment of Inertia : 0.18 kg m ²
Maximum Solid Size : 23 mm	Operating Pressure : 6.194 bar
Pump Weight (Approx) : 47 kg	Maximum Allowable Pressure : 6.469 bar
Pump Standard : EN 733	Minimum Continuous Flow : 33.58 m ³ /h

Motor

Frequency : 50 Hz	Speed : 2900 1/min
Phase : 3~	Degree of Protection : IP 55
Rated Voltage : 415 V	Insulation Class : F
Rated current : 51 A	Frame size : 200 L
Rated Power P2 : 30 kW	

Material of Construction

Flange Connections

Casing : ASTM A743 / A351 CF8	Suction Flange
Impeller : ASTM A743 / A351 CF8	Pressure rating : 16 bar
Stuffing Box : ASTM A743 / A351 CF8	Nominal pipe size : 80
Wear Ring : ASTM A743 / A351 CF8	Standard : PN 16
Bearing Frame : ASTM A48 class 30B	
Shaft : ASTM A276 AISI 304	Discharge Flange
Shaft Sleeve : ASTM A276 AISI 304	Pressure rating : 16 bar
Shaft seal : GLAND PACKING	Nominal pipe size : 65
	Standard : PN 16



C.R.I. PUMPS
Pumping trust. Worldwide.

Performance Curve


Pump Model
ECW 65/200

Project Name : Untitled project 2025-03-22 10:19:23.013

Project ID :

Company Name :
Department :
Phone number :
e-mail address :

Curve Tolerance ISO 9906 Grade 2B



Note:

- i. Performance is not guaranteed except for the rated point.
 - ii. Curves specified are as per Specific gravity and viscosity of water 1.0,
 - iii. Consider NPSH safety margin minimum of 0.5m .
- To select the motor size, read the value of the Power curve at the duty point



C.R.I. PUMPS
Pumping trust. Worldwide.


Dimensional Drawing

Pump Model
ECW 65/200

Project Name : Untitled project 2025-03-22 10:19:23.013

Project ID :

Company Name :
Department :
Phone number :
e-mail address :



In View of continuous developments, The information/specifications/Description/ Illustrations are subject to change without notice.

Dimensions in mm

a	100			H.D(Delivery)	19
b1	440			H.D(Suction)	19
b2	410			No.of Holes-Discharge	4
f	360			No.of Holes-Suction	8
H	295			Nominal Size (ØA)	80
h2	225			Nominal Size (ØB)	65
hA	200			P.C.D(Delivery)	145
L1	1165			P.C.D(Suction)	160
L2	965				
L3	482.5				
Ø A	80				
Ø B	65				
S	14				
X	140				
Z	6				